



NOTE: ON SITE SELECT FILL TO BE RUN OF TRENCH (3\"/>

NOTE: ASPHALT TOP COARSE RESTORATION TO EXTEND 12\"/>

NOTE: A PRESSURE REDUCING VALVE SHALL BE INSTALLED AND SET TO A PRESSURE OF 60 PSI IF THE AVERAGE PRESSURE AT THE METER IS GREATER THAN 60 PSI.

NOTE: ON SITE SELECT FILL TO BE RUN OF TRENCH (3\"/>

NOTE: ON SITE SELECT FILL TO BE RUN OF TRENCH (3\"/>

NOTE: CURB SHALL BE CAST IN PLACE. EXPANSION JOINTS OF 1/2\"/>

NOTE: EXPANSION JOINTS OF 3/16\"/>

NOTE: CURB SHALL BE CAST IN PLACE. EXPANSION JOINTS OF 1/2\"/>

NOTE: ON SITE SELECT FILL TO BE RUN OF TRENCH (3\"/>

NOTE: ON SITE SELECT FILL TO BE RUN OF TRENCH (3\"/>

NOTE: CURB SHALL BE CAST IN PLACE. EXPANSION JOINTS OF 1/2\"/>

NOTE: EXPANSION JOINTS OF 3/16\"/>

NOTE: CURB SHALL BE CAST IN PLACE. EXPANSION JOINTS OF 1/2\"/>

NOTE: ON SITE SELECT FILL TO BE RUN OF TRENCH (3\"/>

NOTE: ON SITE SELECT FILL TO BE RUN OF TRENCH (3\"/>